



Incline Press

The Nautilus Impact Incline Press emphasizes the upper portion of the pectorals while engaging the shoulders and triceps. Its angled pressing path is ideal for members looking to develop upper chest definition and overhead pressing strength. The machine's ergonomic seat, 1:1 weight ratio, and secure Lock N Load® system make it perfect for delivering consistent, safe upper body results in any facility.



FEATURES	
Width	51 in (130 cm)
Length	75 in (191 cm)
Height	60 in (152 cm)
Overall Weight	690 lbs (313 kg)
Shipping weight	814 lbs (369 kg)
ADJUSTMENTS AND MOVEMENTS	
User defined range of motion	Fixed path
Assisted adjustments	Sku Dependent, Gravity assisted positioning, adjustable seat with "easy up" ratcheting adjustment
Color coded pivot points and adjustments	Yes on all units
Unilateral or bilateral movement	Bilateral
Pulley ratio	1:1
FRAME SPECIFICATIONS & CABLE INFORMATION	
Standard frame color options	60 Black
Standard upholstery color options	Black
Frame finish	Electrostatic Powder coating
Customizable paint, upholstery, branding options available	Yes with additional fees and extended lead times
Bolt down locations defined	Yes
Integrated leveling system	No, rubber feet for floor protection
Hardware type	Hex / Button Head
Tubbing thickness	11 ga
USER SPECIFIC INFORMATION	
Static placards	Yes, simple and intuitive placard
Multi-language placards options available	Yes
Grip specifications	Rubber, large grips for pushing, smaller grips for pulling.
Contoured pads	Yes, contoured back pads on select machines
WEIGHT STACK SPECIFICATIONS	
Total stack weight	260 lbs (130 kg)
Incremental weight system	5 lb incremental weight system for optimal progression
Lock N Load® Technology	Our Patented Lock N Load weight stack system uses intuitive, color-coded switches to safely engage weights with a simple flick—no pins to lose, no maintenance required.
Add-on resistance available	Yes, 5lb incremental
Weight stack shroud specifications	Inside and outside steel shrouds, clear windows on both sides
SKUS	

9NA-S2301

